

# Especificaciones



## Eaton 25KBR10

Expulsion fuse-link, medium voltage, 10 A, AC 25 kV, 660 mm, ANSI, K fast, style BR termination

### General specifications

|                             |                                                     |
|-----------------------------|-----------------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Bussmann series medium voltage expulsion fuse |
| <b>CATALOG NUMBER</b>       | 25KBR10                                             |
| <b>EAN</b>                  | 5027590470407                                       |
| <b>PRODUCT LENGTH/DEPTH</b> | 225 mm                                              |
| <b>PRODUCT HEIGHT</b>       | 76 mm                                               |
| <b>PRODUCT WIDTH</b>        | 106 mm                                              |
| <b>PRODUCT WEIGHT</b>       | 23.24 g                                             |
| <b>COMPLIANCES</b>          | ANSI C37.42                                         |



Powering Business Worldwide

## Especificaciones del producto

|                             |                                                                                    |
|-----------------------------|------------------------------------------------------------------------------------|
| AMPERAGE RATING             | 10 A                                                                               |
| CURRENT CHARACTERISTIC TYPE | Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics |
| RATED FREQUENCY - MAX       | 60 Hz                                                                              |
| RATED FREQUENCY - MIN       | 50 Hz                                                                              |
| RELEASE CHARACTERISTIC      | K                                                                                  |
| STANDARD                    | ANSI                                                                               |
| TYPE OF TERMINATION         | Removable buttonhead                                                               |
| VOLTAGE TYPE                | AC                                                                                 |
| COLOR                       | Yellow                                                                             |
| INTERRUPT RATING            | 8 kAIC                                                                             |
| CONSTRUCTION SIZE           | 660 mm                                                                             |
| VOLTAGE RATING              | 25 kV                                                                              |
| TYPE                        | Medium Voltage Expulsion Fuse Link                                                 |
| APPLICATION                 | Primary side transformer protection, feeder protection, capacitor bank protection  |

## Recursos

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



### Eaton Corporation plc

Eaton House  
Carretera 30 Pembroke  
Dublín 4, Irlanda  
Eaton.com

© 2025 Eaton. Todos los derechos reservados.

Follow us on social media to get the latest product and support information.

