

# Especificaciones



## Eaton AHCL530R

Eaton Arrow Hart Color Coded Locking Receptacle, #14-8 AWG, 30A, Industrial, 125V, Back and Side, Yellow, Black, Ultra grip, Glass filled Nylon, L5-30, Two-pole, Three-wire, Glass-filled Nylon, -40C (w/o impact) to 70C (-40F to 158F)

La foto es representativa



### General specifications

|                      |                                                                                      |
|----------------------|--------------------------------------------------------------------------------------|
| PRODUCT NAME         | Eaton Arrow Hart Color Coded Locking Receptacle                                      |
| CATALOG NUMBER       | AHCL530R                                                                             |
| UPC                  | 032664758683                                                                         |
| PRODUCT LENGTH/DEPTH | 1.62 in                                                                              |
| PRODUCT HEIGHT       | 3.64 in                                                                              |
| PRODUCT WIDTH        | 1.12 in                                                                              |
| PRODUCT WEIGHT       | 0.001 lb                                                                             |
| COMPLIANCES          | RoHS Compliant<br>NAFTA                                                              |
| CERTIFICATIONS       | CSA Certified<br>UL Listed<br>NOM<br>Federal Specification<br>Classification 6233 01 |

## Especificaciones del producto

|                              |                              |
|------------------------------|------------------------------|
| <b>SPECIAL FEATURES</b>      | Voltage Color Coding         |
| <b>TYPE</b>                  | Locking Receptacle           |
| <b>AMPERAGE RATING</b>       | 30A                          |
| <b>VOLTAGE RATING</b>        | 125 V                        |
| <b>APPLICATION</b>           | Industrial                   |
| <b>WIRING METHOD</b>         | Back and side                |
| <b>NUMBER OF WIRES</b>       | 3                            |
| <b>NUMBER OF POLES</b>       | Two-pole                     |
| <b>COLOR</b>                 | Yellow<br>Black              |
| <b>MATERIAL</b>              | Glass filled nylon           |
| <b>OPERATING TEMPERATURE</b> | -40 to 70 °C (-40 to 158 °F) |
| <b>ALLOWABLE WIRE SIZE</b>   | #14-8 AWG                    |
| <b>NEMA CONFIGURATION</b>    | L5-30                        |
| <b>TORQUE RATING</b>         | 20 lbf-inch                  |
| <b>DESIGN TYPE</b>           | Ultra grip                   |
| <b>FACE/BODY MATERIAL</b>    | Glass filled nylon           |

## Recursos

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



**Eaton Corporation plc**

Eaton House  
Carretera 30 Pembroke  
Dublín 4, Irlanda  
Eaton.com

© 2025 Eaton. Todos los derechos reservados.

Follow us on social media to get the latest product and support information.

