

Especificaciones



Eaton MDA-20-R

Eaton MDA Series Time-delay fuse 20A, 250 Vac, 125 Vdc, 32 Vdc (self certified), 1.5 kAIC at 250 Vac

General specifications

PRODUCT NAME	Eaton Bussmann series time-delay fuse
CATALOG NUMBER	MDA-20-R
UPC	051712542494
EAN	5027590226509
PRODUCT HEIGHT	32 mm
PRODUCT WEIGHT	2.5 g
COMPLIANCES	CE Marked RoHS Compliant

Especificaciones del producto

AMPERAGE RATING	20 A
MELTING (I2T)	Typical: 483.45
RESISTANCE	0.004065 ohms DC cold
VOLTAGE DROP	0.095 mV typical
INTERRUPT RATING	1.5 kAIC at 250 Vac 10 kAIC at 125 Vac/dc
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end
RESPONSE TIME	60 min at 135%, 120 sec at 200%
MATERIAL	Nickel-plated brass end cap construction Ceramic tube
PACKAGING TYPE	Standard
QUANTITY	5
VOLTAGE RATING	250 Vac, 125 Vdc, 32 Vdc (self certified)
TYPE	Electronic
SPECIAL FEATURES	Ceramic tube
APPLICATION	Electronic circuits

Recursos

PEP ECO-PASSPORT

[EATO-00035-V01.01-EN](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

FECHA:



Eaton Corporation plc

Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
[Eaton.com](#)

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Todos los derechos reservados.