

Locking Devices, Twist-Lock®, Elastogrip, Female Connector Body, 15A 125V, 2-Pole 3-Wire Grounding, L5-15R, Screw Terminal, Water/Dust-Tight Housing

By Hubbell Wiring Device-Kellems
Catalog # [HBL25W47](#)

Locking Devices, Twist-Lock®, Elastogrip®, Female Connector Body, 15A 125V, 2-Pole 3-Wire Grounding, NEMA L5-15R, Screw Terminal, Yellow, Water/Dust-Tight Housing.

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstand 2,000V minimum
- Environmental - Flammability - HB or better per UL94/CSA 22.2 No.0.17
- Environmental - Moisture Resistance - IP20 Suitability
- Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact)
- Mechanical - Terminal Accommodation - #18 AWG- #10 AWG stranded copper wire only.
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498

General

Catalog Number	HBL25W47
Color	Yellow
Cord Range	0.300"-0.655"(7.6-16.6)
EU RoHS Indicator	No
Environmental Conditions	Watertight
Insulation	Insulated Body
Item Type	15A Grounding Elastogrip® Connector
Material	Elastomer / Elastomeric
Material - Mounting Hardware	Cord Mounted
Number Of Poles	2-Pole
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact <ul style="list-style-type: none">Assembly Screws - Steel, zinc platedContacts - BrassStrain Relief Nut - NylonTerminal Retainer - Clear polycarbonateTerminal Screws - Brass
Specifications	
Temperature Rating	Maximum Continuous: 75° C; Minimum Continuous: -40° C w/o impact, -25° with impact.



Type	Connector Body
UPC	783585235912
Dimensions	
Dimensions	1.76 in x 1.76 in x 4.03 in
Display Size	Standard
Height	4.03 in
Length	1.76 in
Weight	0.35 lb
Width	1.76 in
Electrical Ratings	
Amperage Rating	15 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	15 A
Current Rating	15 A
Dielectric Strength	Withstands 2,000V minimum
Voltage Rating	125 VAC
Voltage Rating Description	125 VAC
Conductor Related	
Cable Range	0.300 - 0.655 in
Number Of Wires	3-Wire
Wire Size	#18 AWG to #10 AWG
Certifications And Compliance	
Industry Standard(s)	<ul style="list-style-type: none">Certified to CSA C22.2 No.42Fed.Spec. W-C-596Listed to UL 498
Nema Rating	L6-15R
Logistics	
Carton Quantity	10
Pallet Quantity	1200
Product Assets	



A Hubbell brand