



Locking Devices, Industrial, Flanged Inlet, 30A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, L15-30P, Screw Terminal, White

By Bryant  
Catalog # 71530MB

Locking Devices, Industrial, Flanged Inlet, 30A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, L15-30P, Screw Terminal, White

Application

Extra Heavy Duty Industrial

General

|                              |                                                                        |
|------------------------------|------------------------------------------------------------------------|
| Catalog Number               | 71530MB                                                                |
| Color                        | White                                                                  |
| EU RoHS Indicator            | Yes                                                                    |
| Environmental Conditions     | Indoor Dry Unless Protected By Additional Means                        |
| Insulation                   | Insulated Body                                                         |
| Item Type                    | 30A Flanged Inlet                                                      |
| Material                     | Composite                                                              |
| Material - Mounting Hardware | Screw Mounting                                                         |
| Number Of Poles              | 3-Pole                                                                 |
| Style                        | Equipment Base                                                         |
| Temperature Rating           | Maximum Continuous: 75° C;<br>Minimum Continuous: -40° C<br>w/o impact |
| Type                         | Flanged Inlet                                                          |
| UPC                          | 781786696167                                                           |

Dimensions

|              |                             |
|--------------|-----------------------------|
| Dimensions   | 2.88 in x 2.88 in x 2.02 in |
| Display Size | Standard Sized Product      |
| Height       | 2.02 in                     |
| Length       | 2.88 in                     |



Width2.88 in

Electrical Ratings

|                            |                  |
|----------------------------|------------------|
| Amperage Rating            | 30 A             |
| Connectivity               | Screw Terminals  |
| Current Rating             | 30 A             |
| Dielectric Strength        | Withstands 3500V |
| Voltage Rating             | 3 Phase 250 VAC  |
| Voltage Rating Description | 3 Phase 250V AC  |

Conductor Related

|                 |                   |
|-----------------|-------------------|
| Number Of Wires | 4-Wire            |
| Wire Size       | #14 AWG to #8 AWG |

Certifications And Compliance

|                                    |         |
|------------------------------------|---------|
| Nema Rating                        | L15-30P |
| Standards - RoHS Compliance Status | CM      |

Logistics

|                 |    |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Product Assets

[Catalogs - Bryant Full Line Catalog](#)  
[Specifications - 71530MB](#)